

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

1. Identification of the substance/preparation and of the company/undertaking

Trade name : Bardac LF-70

Street address : Lonza Ltd
Muenchensteinerstrasse 38
CH-4002 Basel, Switzerland
Telephone: +41 61 316 81 11

Emergency telephone number : Lonza Ltd, CH-4002 Basel, Switzerland
Telephone: +41 61 313 94 94 (24h)

2. Composition/information on ingredients

Components / EC Label	Concentration
Dimethyldioctylammonium chloride (CAS-No.: 5538-94-3) (EEC-No.: 226-901-0) C, N; R22, R34, R50	ca. 70 %
Propan-2-ol (CAS-No.: 67-63-0) (EEC-No.: 200-661-7) F, Xi; R11, R36, R67	ca. 10 % (*)
Water (CAS-No.: 7732-18-5) (EEC-No.: 231-791-2)	ca. 20 %

R-phrases see chapter 16

(*) Components with workplace control parameters see chapter 8

3. Hazards identification

Classification

Flammable.
Harmful if swallowed.
Causes burns.
Very toxic to aquatic organisms.

4. First aid measures

Inhalation : Move to fresh air. Call a physician immediately. If breathing is irregular or stopped, administer artificial respiration.

Skin contact : After contact with skin, wash immediately with plenty of soap and water. Call a physician immediately. Take off all contaminated clothing immediately.

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

- Eye contact : Immediately flush eye(s) with plenty of water. Call a physician immediately.
- Ingestion : Call a physician immediately. Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

Notes to physician

- Symptoms : Causes severe irritation of eyes, skin and mucous membranes.

5. Fire-fighting measures

- Suitable extinguishing media : Dry powder, Water spray, Foam
- Specific hazards during fire fighting : Heating or fire can release toxic gas.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
- Additional advice : Use water spray to cool unopened containers.

6. Accidental release measures

- Personal precautions : Use respirator when performing operations involving potential exposure to vapour of the product.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

7. Handling and storage

Handling

- Safe handling advice: : Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust in work rooms.
- Advice on protection against fire and explosion : Highly flammable. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Storage

- Requirements for storage areas and containers : Keep container tightly closed. To maintain product quality, do not store in heat or direct sunlight. Keep in a dry, cool and well-ventilated place.

8. Exposure controls / personal protection

Components with workplace control parameters

Propan-2-ol (CAS-No. 67-63-0):

DFG-MAK/BAT/TRK-Value-List Germany (2002)

- Exposure limit(s) : 200 ml/m³ 500 mg/m³
Damage to fetus unlikely if the occupational exposure limit values are not exceeded.
- Short term exposure limit : Peak-limit category II(2)

Switzerland SUVA Limit Values (2003)

- Exposure limit(s) : 200 ml/m³ 500 mg/m³
Damage to fetus unlikely if the occupational exposure limit values are not exceeded.
Biological monitoring
- Short term exposure limit : 400 ml/m³ ; 1 000 mg/m³
4 times 15 min. per shift

US ACGIH

- Exposure limit(s) : 200 ml/m³
Carcinogenicity: group A4
- Short term exposure limit : 400 ml/m³

- IDLH value : 2 000 ppm

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

Personal protective equipment

Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.
Respiratory protection	:	In the case of vapour formation use a respirator with an approved filter.
Hand protection	:	Wear suitable gloves.
Eye protection	:	Wear eye/face protection.
Skin and body protection	:	Wear suitable protective clothing, gloves and eye/face protection.

9. Physical and chemical properties

Appearance

State of aggregation	:	liquid
Colour	:	light yellow
Odour	:	aromatic

Safety data

pH	:	6,5 - 8 (10 g/l ; 20 °C)
Setting point	:	< 5 °C
Flash point	:	ca. 30 °C
Density	:	0,915 g/cm ³ (20 °C)
Water solubility	:	completely miscible
Viscosity, dynamic	:	35 mPa.s (20 °C)

10. Stability and reactivity

Conditions to avoid:	:	no data available
Hazardous reactions	:	Stable under normal conditions.

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

11. Toxicological information

Acute oral toxicity (LD50)	:	200 - 2 000 mg/kg Species: rat
Skin irritation	:	Corrosive Species: rabbit
Eye irritation	:	Corrosive Species: rabbit

12. Ecological information

The following ecotoxicological data refer to:

N,N-Dioctyl-N,N-dimethylammonium chloride (CAS-No.: 5538-94-3)

Ecotoxicity effects

Toxicity to fish (LC50)	:	0,35 mg/l Species: Oncorhynchus mykiss (rainbow trout) Acute toxicity Exposure time: 96 h Method: US-EPA
Toxicity to fish	:	0,55 mg/l Species: Bluegill sunfish Acute toxicity Exposure time: 48 h Method: US-EPA
Toxicity (other route) (LC50)	:	> 2 500 ppm Species: Mallard duck Subacute toxicity Exposure time: 8 d
Toxicity (other route) (LC50)	:	1 300 ppm Species: Bobwhite quail Subacute toxicity Exposure time: 8 d

Persistence and degradability

Biodegradability	:	OECD Confirmatory Test: > 89 % Testing period: 10 - 51 d Method: OECD 303 A
------------------	---	---

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

CO2 Evolution Test: 86 %

Testing period: 28 d

Method: OECD 301 B

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

13. Disposal considerations

- Waste from residues : The organic ingredients can be incinerated in a suitable installation when in accordance with local regulations.
- Contaminated packaging : Where possible recycling is preferred to disposal or incineration.

14. Transport information

- ADR : Class: 8
Packaging group: II
Classification Code: CF1
Labels: Corrosive substance No. 8
Flammable liquid No. 3
- Risk No. : 83
- UN/ID No. : UN 2920
- Proper shipping name : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Dioctyldimethylammonium chloride; Isopropanol)

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

RID : Class: 8
Packaging group: II
Classification Code: CF1
Labels: Corrosive substance No. 8
Flammable liquid No. 3
Risk No. : 83
UN/ID No. : UN 2920
Proper shipping name : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Dioctyldimethylammonium chloride; Isopropanol)

IATA Cargo : Class: 8
Packaging group: II
Labels: Corrosive substance No. 8
Flammable liquid No. 3
Packing instruction (cargo aircraft): 812
UN/ID No. : UN 2920
Proper shipping name : Corrosive liquid, flammable, n.o.s.
(Dioctyldimethylammonium chloride; Isopropanol)

IATA Passenger : Class: 8
Packaging group: II
Labels: Corrosive substance No. 8
Flammable liquid No. 3
Packing instruction (passenger and cargo aircraft): 808
UN/ID No. : UN 2920
Proper shipping name : Corrosive liquid, flammable, n.o.s.
(Dioctyldimethylammonium chloride; Isopropanol)

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

IMDG-Code : Class: 8
Packaging group: II
Labels: Corrosive substance No. 8
Flammable liquid No. 3
EmS: F-E , S-C

UN/ID No. : Marine pollutant: yes
UN 2920
Proper shipping name : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Diocetyl dimethylammonium chloride; Isopropanol)

49 CFR : Class: 8
Packaging group: II
Labels: Corrosive substance No. 8
Flammable liquid No. 3

UN/ID No. : UN 2920
Proper shipping name : Corrosive liquids, flammable, n.o.s.
(Diocetyl dimethylammonium chloride; Isopropanol)

TDG : Class: 8
Packaging group: II
Labels: Corrosive substance No. 8
Flammable liquid No. 3

UN/ID No. : UN 2920
Proper shipping name : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Diocetyl dimethylammonium chloride; Isopropanol)

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

15. Regulatory information

Additional advice : Classification and labelling according to Directive 1999/45/EC.


Symbol(s) :



Corrosive



Dangerous for the environment



R-phrase(s)

R10: Flammable.
R22: Harmful if swallowed.
R34: Causes burns.
R50: Very toxic to aquatic organisms.

S-phrase(s)

S16: Keep away from sources of ignition - No smoking.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28: After contact with skin, wash immediately with plenty of soap and water.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61: Avoid release to the environment. Refer to special instructions/safety data sheets.

National legislation

Water contaminating class (Germany) : WGK 2: water endangering

16. Other information

Other regulations : The components of this product are reported in the following inventories: EINECS, TSCA.

Safety Data Sheet

Bardac LF-70

Version: 01.12.2006 / EN

R-phrases(s)

R11	:	Highly flammable.
R22	:	Harmful if swallowed.
R34	:	Causes burns.
R36	:	Irritating to eyes.
R50	:	Very toxic to aquatic organisms.
R67	:	Vapours may cause drowsiness and dizziness.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.